

PRODUCT DATASHEET

Last information update: May 2023




ARKOS

0820W45

Architectural LED floodlight for outdoor applications


Technical Features

| | |
|-------------------------|----------------------|
| Power | 45W |
| Input voltage | AC100-240V |
| Insulation class | I |
| Delivered flux | 1,580 lm ±10% |
| Light distribution type | symmetrical |
| Beam angle | ultra spot 2.5° |
| Light colour / CCT | RGBW |
| CRI | - |
| Source type | LED |
| LED number | 9 |
| MacAdam step | - |
| Power supply | Built-in |
| Control | DMX512 |
| Protection index | IP66 |
| Impact resistance | IK08 |
| Lifetime | 50,000 hours Ta=25°C |



Wiring

Power input cable OPEN END 500mm
 DMX input cable MALE connector 500mm
 DMX output cable FEMALE connector 500mm



Construction

Fluorocarbonate powder painted die-cast aluminum body, tempered glass cover, polycarbonate optical lenses.

Temperature Limits

| | |
|-------------------------------|---------------------|
| Ambient operating temperature | from -20°C to +50°C |
| Storage temperature | from -40°C to +70°C |


Installation

Surface mounted with adjustable base.

Finish Colours


RAL9023 as standard colour, other RAL colours on request.

Optional Accessories



built-in anti-glare accessory for improved visual comfort
*can not be ordered separately

honeycomb




anti-glare accessory for improved visual comfort
*can not be ordered separately

anti-glare glass




mounting accessory
*can not be ordered separately



U-bracket




mounting accessory for Ø 48mm poles
*can not be ordered separately



pole adapter




mounting accessory for Ø 114mm poles
*can not be ordered separately



pole clamp




mounting accessory for Ø 67~325mm T>=4 poles
*can not be ordered separately



pole plate




mounting accessory for Ø 168~268mm trees
*can not be ordered separately




strap



mounting accessory
*can not be ordered separately




spike



with female 4-pin waterproof connector for DMX
* specify cable length to complete order

leader cable



with male and female 4-pin waterproof connector for DMX
* specify cable length to complete order

extension cable

Ordering Information

example: **0820W45.0002.RGB30K.01+A1**

0820W45 · [] · [] · [] + []

| product | beam angle | light colour / CCT | finish colour | accessory |
|-------------------------|------------|-------------------------|---------------|----------------------------|
| ARKOS 45W ULTRA SPOT | 0002 2.5° | RGB30K RGB+3000K | 01 RAL9023 | A1 honeycomb |
| | | RGB40K RGB+4000K | | A2 anti-glare glass |
| | | | | A3 U-bracket |
| | | | | A4 pole adapter |
| | | | | A5 pole clamp |
| | | | | A6 pole plate |
| | | | | A7 strap |
| | | | | A8 spike |
| | | | | LC4 leader cable |
| | | | | EC4 extension cable |