

## PRODUCT DATASHEET

Last information update: May 2023




### HIGHLAND

0821W300

Architectural LED floodlight for outdoor applications

#### Technical Features

Power	300W
Input voltage	AC100-240V
Insulation class	I
Delivered flux	15,000 lm ±10%
Light distribution type	symmetrical
Beam angle	ultra spot 2.5°
Light colour / CCT	2700K, 3000K, 4000K
CRI	80
Source type	LED
LED number	90
MacAdam step	5
Power supply	Built-in
Control	ON/OFF
Protection index	IP66
Impact resistance	IK08
Lifetime	50,000 hours Ta=25°C



#### Construction

Fluorocarbonate powder painted die-cast aluminum body, tempered glass cover, polycarbonate optical lenses.

#### Temperature Limits

Ambient operating temperature	from -20°C to +50°C
Storage temperature	from -40°C to +70°C

#### Installation

Surface mounted with adjustable bracket.

#### Finish Colours


RAL9023 as standard colour, other RAL colours on request.

#### Wiring

Power input cable OPEN END 500mm



Optional Accessories




built-in anti-glare accessory for improved visual comfort  
\*can not be ordered separately

honeycomb



anti-glare accessory for improved visual comfort  
\*can not be ordered separately



visor

Ordering Information

example: 0821W300.0002.2780.01+A1

0821W300 · [ ] · [ ] · [ ] + [ ]

product	beam angle	light colour / CCT	finish colour	accessory
HIGHLAND 300W ULTRA SPOT	0002 2.5°	2780 2700K RA80	01 RAL9023	A1 honeycomb
		3080 3000K RA80		A2 visor
		4080 4000K RA80		