

PRODUCT DATASHEET

Last information update: May 2023




ARC-SIDE

1915W3

Inground LED marker light for outdoor applications

Technical Features

Power	3W
Input voltage	DC24V (constant voltage)
Insulation class	III
Delivered flux	180 lm ±10%
Light distribution type	symmetrical, 1-emission
Beam angle	60°
Light colour / CCT	2700K, 3000K, 4000K
CRI	80
Source type	LED
LED number	1
MacAdam step	5
Power supply	Not included
Control	ON/OFF
Protection index	IP67
Impact resistance	IK10
Walk over	yes
Drive over	yes
Lifetime	50,000 hours Ta=25°C



Construction

Stainless steel body, engineering plastic recessed box, polycarbonate optical lenses.

Temperature Limits

Ambient operating temperature	from -20°C to +50°C
Storage temperature	from -40°C to +70°C

Installation

Ground recessed with recessed box.

Finish Colours

Stainless steel as standard colour. RAL colours on request.

Wiring

Power input cable OPEN END 500mm



Ordering Information

example: **1915W3.0060.2780.01**

1915W3 · [] · [] · [] + []

product	beam angle	light colour / CCT	finish colour
ARC-SIDE 3W 1-EMISSION	0060 60°	2780 2700K RA80	01 stainless steel
		3080 3000K RA80	
		4080 4000K RA80	

PRODUCT DATASHEET

Last information update: May 2023




ARC-SIDE

1915W3(220V)

Inground LED marker light for outdoor applications

Technical Features

Power	3W
Input voltage	AC100-240V
Insulation class	I
Delivered flux	180 lm ±10%
Light distribution type	symmetrical, 1-emission
Beam angle	60°
Light colour / CCT	2700K, 3000K, 4000K
CRI	80
Source type	LED
LED number	1
MacAdam step	5
Power supply	built-in
Control	ON/OFF
Protection index	IP67
Impact resistance	IK10
Walk over	yes
Drive over	yes
Lifetime	50,000 hours Ta=25°C



Construction

Stainless steel body, engineering plastic recessed box, polycarbonate optical lenses.

Temperature Limits

Ambient operating temperature	from -20°C to +50°C
Storage temperature	from -40°C to +70°C

Installation

Ground recessed with recessed box.

Finish Colours

Stainless steel as standard colour. RAL colours on request.

Wiring

Power input cable OPEN END 500mm



Ordering Information

example: **1915W3(220V).0060.2780.01**

1915W3(220V) · · · +

product	beam angle	light colour / CCT	finish colour
ARC-SIDE 3W 1-EMISSION	0060 60°	2780 2700K RA80	01 stainless steel
		3080 3000K RA80	
		4080 4000K RA80	