

PRODUCT DATASHEET

Last information update: May 2023




SERRA

0811W45

Architectural LED floodlight for outdoor applications

Technical Features

Power	45W
Input voltage	AC100-240V
Insulation class	I
Delivered flux	2,250 lm ±10%
Light distribution type	symmetrical
Beam angle	ultra spot 2.5°
Light colour / CCT	2700K, 3000K, 4000K
CRI	80
Source type	LED
LED number	5
MacAdam step	5
Power supply	Built-in
Control	ON/OFF
Protection index	IP66
Impact resistance	IK08
Lifetime	50,000 hours Ta=25°C



Construction

Fluorocarbon painted die-cast aluminum body, tempered glass cover, polycarbonate optical lenses.

Temperature Limits

Ambient operating temperature	from -20°C to +50°C
Storage temperature	from -40°C to +70°C

Installation


Surface mounted with adjustable base.

Finish Colours









RAL9023 as standard colour, other RAL colours on request.

Wiring

Power input cable OPEN END 500mm



Optional Accessories

	built-in anti-glare accessory for improved visual comfort *can not be ordered separately	honeycomb	
	anti-glare accessory for improved visual comfort *can not be ordered separately	anti-glare glass	
	mounting accessory *can not be ordered separately		U-bracket
	mounting accessory for \varnothing 48mm poles *can not be ordered separately		pole adapter
	mounting accessory for \varnothing 114mm poles *can not be ordered separately		pole clamp
	mounting accessory for \varnothing 67~325mm T>=4 poles *can not be ordered separately		pole plate
	mounting accessory for \varnothing 168~268mm trees *can not be ordered separately		strap
	mounting accessory *can not be ordered separately		spike

Ordering Information

example: 0811W45.0002.2780.01+A1

0811W45 · [] · [] · [] + []

product	beam angle	light colour / CCT	finish colour	accessory
SERRA	0002 2.5°	2780 2700K RA80	01 RAL9023	A1 honeycomb
45W ULTRA SPOT		3080 3000K RA80		A2 anti-glare glass
		4080 4000K RA80		A3 U-bracket
				A4 pole adapter
				A5 pole clamp
				A6 pole plate
				A7 strap
				A8 spike